

6390 Philips Highway Jacksonville, FL 32216 Phone (904) 737-7144

SPECIFICATION DATA SHEET

Drawn by: M.D.C.

Date: 07/26/12 rev.

MODEL No. 3211-DS2

SIZES 4" - 12" DIAMETERS CONICAL TAKEOFF WITH INSULATION GUARD, MANUAL VOLUME DAMPER WITH HANDLE STANDOFF, SOLID ROD DAMPER AXIS

DIMENSIONAL DATA

SIZES AVAILABLE: 4" THROUGH 12" DIAMETER

CONICAL CONNECTION HOLE TO TRUNK DUCT IS APPROXIMATELY 2" GREATER THAN BRANCH DUCT DIMENSION.

FABRICATION DATA

MATERIAL:

FABRICATED FROM HOT DIPPED GALVANIZED STEEL SHEETS PER ASTM-A653 CS TYPE B.

SIZE BODY DAMPER BLADE 4" - 8" 28 GA. 24 GA. 9" - 12" 26 GA. 24 GA.

FEATURES


CONTINUOUS WELD LONGITUDINAL SEAM FOR NO AIR LEAKAGE @ 2" W.G. STATIC PRESSURE.

1" WIDE FLANGE WITH GASKET

5 3/8" LONG COLLAR.

SIZES 4" THROUGH 12": 3/8" CONTINUOUS ROD DAMPER AXIS WITH LOCKING REGUALTOR, NYLON GROMMETS INSTALLED AT THE COLLAR PENETRATIONS.

2" DAMPER HANDLE STANDOFF.



OPTIONS

SPECIAL NOTES

RECOMMENDED INSTALLATION: DAMPER AXIS PARALLEL TO AIR FLOW.

MADE TO MEET S.M.A.C.N.A. GAUGE STANDARDS. MAXIMUM 2" W.G. STATIC PRESSUDE SCHEDULE. (S.M.A.C.N.A. HVAC DUCT CONSTRUCTION STANDARDS, SECOND EDITION-1995)

NOTE BRANCH DUCT DIMENSION WHEN ORDERING.