

6390 Philips Highway Jacksonville, FL 32216 Phone (904) 737-7144

## SPECIFICATION DATA SHEET

Date: 07/26/12 rev.

Drawn by: M.D.C.

# **MODEL No. 3310-DS2**

SIZES 6" - 12" DIAMETERS
TAKEOFF COLLAR FOR ROUND PIPE WITH GASKET
FLANGE, MANUAL VOLUME DAMPER WITH HANDLE
STANDOFF, SOLID ROD DAMPER AXIS

#### **DIMENSIONAL DATA**

SIZES AVAILABLE: 6" THROUGH 12"

COLLAR LENGTH: 6"

1- 1/2" WIDE FLANGE.

#### **FABRICATION DATA**

MATERIAL:

FABRICATED FROM HOT DIPPED GALVANIZED STEEL SHEETS PER ASTM-A653 CS TYPE B.

SIZE BODY DAMPER BLADE

6" - 8" 28 GA. 24 GA. 9" - 12" 26 GA. 24 GA.


### **FEATURES**

CONTINUOUS WELD LONGITUDINAL SEAM FOR NO AIR LEAKAGE AT 2" W.G. STATIC PRESSURE.

FLANGE WITH GASKET AND PRE-DRILLED SCREW HOLES FOR EASE OF INSTALLATION.

DAMPER TO HAVE A 3/8" SQUARE CONTINUOUS ROD AXIS WITH LOCKING REGULATOR, NYLON GROMMETS INSTALLED AT THE COLLAR PENETRATIONS.

2" DAMPER HANDLE STANDOFF.



#### **SPECIAL NOTES**

RECOMMENDED INSTALLATION: DAMPER AXIS PARALLEL TO AIR FLOW.

MADE TO MEET S.M.A.C.N.A. GAUGE STANDARDS. MAXIMUM 2" W.G. STATIC PRESSUDE SCHEDULE. (S.M.A.C.N.A. HVAC DUCT CONSTRUCTION STANDARDS, SECOND EDITION-1995)